

- ◆ 符合ISO228标准
- ◆ 由含钨工具钢制成, 油淬火, 超低温处理
- ◆ 产品的耐磨性好, 寿命长, 尺寸稳定, 光洁度高
- ◆ 硬度HRC60-62



535-0250-01



536-0250-01

量 规

货号(GO)	货号(NOGO)		规格
	等级B	等级A	
535-0125-01	536-0125-01	536-0125-01A	G1/8-28
535-0250-01	536-0250-01	536-0250-01A	G1/4-19
535-0375-01	536-0375-01	536-0375-01A	G3/8-19
535-0500-01	536-0500-01	536-0500-01A	G1/2-14
535-0625-01	536-0625-01	536-0625-01A	G5/8-14
535-0750-01	536-0750-01	536-0750-01A	G3/4-14
535-0875-01	536-0875-01	536-0875-01A	G7/8-14
535-1000-01	536-1000-01	536-1000-01A	G1-11

货号(GO)	货号(NOGO)		规格
	等级B	等级A	
535-1125-01	536-1125-01	536-1125-01A	G1-1/8-11
535-1250-01	536-1250-01	536-1250-01A	G1-1/4-11
535-1500-01	536-1500-01	536-1500-01A	G1-1/2-11
535-1750-01	536-1750-01	536-1750-01A	G1-3/4-11
535-2000-01	536-2000-01	536-2000-01A	G2-11
535-2500-01	536-2500-01	536-2500-01A	G2-1/2-11
535-3000-01	536-3000-01	536-3000-01A	G3-11
535-4000-01	536-4000-01	536-4000-01A	G4-11