

花岗岩平板

611系列




- ◆ 符合JJG平板国家计量检定规程和德国标准DIN876
- ◆ 采用天然花岗岩, 尺寸稳定, 受温度影响小
- ◆ 00级适用于检验室, 0级适用于车间
- ◆ 带生产厂检定报告
- ◆ 可定制其他大尺寸平板



611-042-00

花岗岩物理特性

肖氏硬度	94HS
抗弯曲强度	28MPa
抗压缩强度	236MPa
弹性模量	$9.88 \times 10^4 \text{MPa}$
泊松比	0.33
体积密度	3000kg/m^3
吸水率	0.05%
线性膨胀系数	$6 \times 10^{-6} / ^\circ\text{C}$



JJG 0级(DIN87600级)

货号	尺寸(LxWxH)	平面度	重量(Kg)
611-032-00	300x200x60mm	2.7μm	11
611-042-00	400x250x60mm	2.9μm	18
611-044-00	400x400x60mm	3.1μm	29
611-053-00	500x315x70mm	3.2μm	33
611-064-00	630x400x80mm	3.5μm	60
611-066-00	630x630x100mm	3.8μm	119
611-085-00	800x500x100mm	3.9μm	120
611-106-00	1000x630x140mm	4.4μm	265
611-107-00	1000x750x150mm	4.5μm	337
611-101-00	1000x1000x150mm	4.8μm	450
611-121-00	1200x800x160mm	4.9μm	461
611-161-00	1600x1000x180mm	5.8μm	864
611-201-00	2000x1000x220mm	6.5μm	1320
611-215-00	2000x1500x250mm	7.0μm	2250

JJG 1级(DIN8760级)

货号	尺寸(LxWxH)	平面度	重量(Kg)
611-032-10	300x200x60mm	5.4μm	11
611-042-10	400x250x60mm	5.9μm	18
611-044-10	400x400x60mm	6.3μm	29
611-053-10	500x315x70mm	6.4μm	33
611-064-10	630x400x80mm	7.0μm	60
611-066-10	630x630x100mm	7.6μm	119
611-085-10	800x500x100mm	7.8μm	120
611-106-10	1000x630x140mm	8.7μm	265
611-107-10	1000x750x150mm	9.0μm	337
611-101-10	1000x1000x150mm	9.7μm	450
611-121-10	1200x800x160mm	9.8μm	461
611-161-10	1600x1000x180mm	11.5μm	864
611-201-10	2000x1000x220mm	12.9μm	1320
611-215-10	2000x1500x250mm	14.0μm	2250